



## 5W-30 SN/CF

REV 02-27.02.2024

5W-30 SN/CF is an advanced full synthetic oil for both petrol and diesel engines to combat the challenges faced by engines exposed to both high and low temperature at high pressure conditions.

### Application Recommendation

5W-30 can be used in 4-stroke gasoline engines, four-valve and 4-stroke diesel engines with or without turbo. It complies with API SN.

### Performance Features

- Mid-SAPS allows for a cleaner engine and longer drain intervals, guaranteeing longer engine life.
- Superior wear and bearing corrosion giving maximum engine protection.
- Premium soot and sludge handling.

### Performance levels

Meets the Approvals of high performance: API SN/CF specifications PCMO, ACEA A3/B4, MB 229.3, VW 502.00/505.00, Renault 710/700, PSA B71 –2300

### Typical Physical Properties

PROPERTIES	UNITS	VALUE
Density @ 20°C	g/ml	0.850
Viscosity index	none	166
Viscosity @ 40°C	cSt	67
Viscosity @ 100°C	cSt	11
Pour Point	°C	-48

### Handling and Storage

#### Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

#### Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Additional information-Storage

#### Additional information

Product, contaminated rags and paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose off dirty material used to absorb safely after use.

### Product Warranty

**Industrial lubricants are formulated to meet or exceed industrial specifications and carries a warranty. The purchaser /end user is responsible for determining if these specifications are adequate and proper for the intended application. The warranty is limited to lubricant performance consistent with indicated specifications. No additional warranty, expressed or implied can be made.**