

HYD 68

Evolution Oils Hydraulic 68 is a high quality fluid which provides lucrative and reliable protection in most industrial and mobile applications.

Application Recommendation

Evolution Oils Hydraulic 68 is recommended for use in a wide variety of industrial, mobile and mining hydraulic system applications and provides improved ageing resistance, corrosion & wear protection.

Performance Features

- Hydrolytically stable.
- Excellent anti-wear characteristics.
- Offers resistance to oxidation.

Performance levels

Meets the Approvals of Vickers I-286-S & M-2950-S, B.F. Goodrich, Cincinnati Milacron P-68, P-69 & P-70, Racine & variable volume vane, US Steel 136 & 127, Ford M-6C32, DIN 51524 & part 2, Denison HF-1, HF-2 & HF-0 and General Motors LH-04-1, LH-06-1 & LH-15-1

Typical Physical Properties

PROPERTIES	UNITS	VALUES
Density @ 20°C	g/ml	0.872
Viscosity index	none	103
Viscosity @ 40°C	cSt	68.7
Viscosity @ 100°C	cSt	8.9
Pour Point	°C	-21

Handling and Storage

Handling

Avoid prolonged or repeated contact with skin. Wash thoroughly after handling.

Storage

Keep container tightly closed. Keep container in a cool, well-ventilated area. Store under cover away from heat and sources of ignition. Additional information-Storage

Additional information

Product, contaminated rags and paper or material used to absorb spillages represent a fire hazard and should not be allowed to accumulate. Dispose off dirty material used to absorb safely after use.

Product Warranty

Industrial lubricants are formulated to meet or exceed industrial specifications and carries a warranty. The purchaser /end user is responsible for determining if these specifications are adequate and proper for the intended application. The warranty is limited to lubricant performance consistent with indicated specifications. No additional warranty, expressed or implied can be made.